

OFFICE OF THE MARION COUNTY SUR	RVEYOR			
SECTION RECORD CORNER SECTION 27 TOWNSHIP 16	RANGE	5		
DATE:10=4-96 10-02-03	_ KINGL_			-
PARTY CHIEF: Wilcoxen			Line of 25th	2500 N
CREW:			LINE UT ESTI	E300 N
TYPE OF MARKER: Harrison	See Note			L
METHOD OF ESTABLISHMENT: Count	yı 2-13-90			
IN. S.P.C. E ZONE, NAD 83				9
NAME: 16052706 1-70		,		1
N: 505875.4870(m)				4
Ei 75494,1600(m)	0 E			4 3
NOTE: There are sign	8			N
posts beside Harrison.	□			
	County Line 12000			
	4	1.		
3,	5	K.		
	3			
×		X-	Line of 25t	h St.
4. 176.53		2.		
H 1				

Original wooden post set 1820 by Hendricks with witnesses: 22" maple S 59W 11 links, 10" elm N 68 E 20 links per Marion County Atlas pg. 15. Legal Survey 8-9/1854 used corner for line, (made no calls nor witnesses per Warren Township Legal Survey Book pg. 11 & 12. 4-14-1863 Voorhis called distances from center of 27 to E Q; no description or ties provided per Warren Township Legal Survey Book, pg 30. MCS received request to re-establish 1989. Stone fd near calculated position of corner. Excavated S Q fd to be carved on E face of stone. Hancock Surveyor ofc contacted us 2-20-90. Hancock removed stone and placed Harrison in its place. The removed stone is on display in the Office of the Marion County Surveyor.

HC652706

REF.	DISTANCE	DESCRIPTION		
1.	6.00′	Rebar		
2.	6.00′	Rebar		
3.	5.40′	1 1/2° pipe 1'N of fence line		
4.	176.53'	NE corner foundation #2457 Borgman Drive		
-				